




3C XLPE Insulated Medium Voltage Cables 19/33kV, AL



Note: The above drawing is for representation purpose only.

Description

Conductor:	Class 2 Aluminium
Conductor Screen:	Semi-conductive Compound
Insulation:	XLPE
Insulation Screen:	Semi-conductive Compound
Metallic Screen:	Plain Annealed Copper Wire
Sheath:	PVC 5V-90

Core Identification

Red, White, Blue

Sheath Colour

Black

Technical Data

Voltage Rating:	19/33kV
Operating Temperature:	-25°C to +90°C
Short Circuit Temperature:	250°C for 5 sec

Standards Compliance

AS/NZS 1429.1	AS/NZS 3808
AS/NZS 1125	AS/NZS 1660.5.6 (Equivalent to IEC 60332-1)


Characteristics



FLAME RETARDANT



UV STABILISED



-25°C ~ +90°C



GREEN STAR

The information in this specification is to be used as a guide only. World Wire Cables (Aust) Pty Ltd has taken all due care in compiling the information in this specification but accepts no responsibility for any errors or omissions. All information provided in this specification is covered by copyright.





3C XLPE Insulated Medium Voltage Cables 19/33kV, AL

Physical & Electrical Characteristics

WWC Product Code	Conductor Size (mm ²)	Conductor Diameter (mm)	Insulation Thickness (mm)	Approx. Overall Diameter (mm)	Min. Bending Radius (mm)		Approx. Weight (kg/m)
					During Installation	After Installation	
*SMMV33A4X3C50	50	8.30	8.0	69.5	1352	901	3.9
*SMMV33A6X3C70	70	9.95	8.0	73.2	1424	949	4.6
*SMMV33A9X3C95	95	11.60	8.0	77.2	1501	1001	5.3
*SMMV33A10X3C120	120	13.03	8.0	80.5	1564	1043	5.8
*SMMV33A10X3C150	150	14.57	8.0	84.0	1633	1088	6.4
*SMMV33A10X3C185	185	16.18	8.0	87.7	1705	1136	7.0
*SMMV33A10X3C240	240	18.43	8.0	93.0	1807	1205	8.0
*SMMV33A10X3C300	300	20.61	8.0	97.9	1903	1268	9.0
*SMMV33A10X3C400	400	23.79	8.0	105.3	2047	1364	9.7
*SMMV33A10X3C500	500	27.20	8.0	113.1	2198	1465	10.7

© World Wire Cables (Aust) Pty Ltd. All Rights Reserved.

*These cables are non-stocked items subject to lead times.

Cond. Size (mm ²)	Max. D.C. Resistance of cond. at 20°C (Ω/km)	A.C. Resistance of cond. at 90°C, 50Hz (Ω/km)	Operating Induct. (mH/km)	Mutual Capa. (μF/km)	Fault Current Rating (kA/s)		+Current-carrying capacity (A)			
					Cond.	Screen	In Air Touching	In Air Enclosed	In Ground	In ground Enclosed
50	0.641	0.822	0.488	0.143	4.7	4.7	164	123	164	133
70	0.443	0.568	0.465	0.157	6.6	6.8	200	159	200	169
95	0.320	0.411	0.444	0.171	9.0	9.0	241	190	236	200
120	0.253	0.325	0.429	0.185	11.3	10.1	277	215	272	231
150	0.206	0.265	0.415	0.200	14.2	10.1	318	241	302	256
185	0.164	0.211	0.403	0.213	17.5	10.1	359	277	343	292
240	0.125	0.161	0.388	0.234	22.7	10.1	425	318	400	338
300	0.100	0.130	0.377	0.252	28.3	10.1	482	364	451	379
400	0.0778	0.1016	0.364	0.277	37.8	10.1	564	436	513	451
500	0.0617	0.0816	0.354	0.314	47.3	10.1	650	492	585	510

*Based on ambient air temperature of 40°C, soil temperature of 25°C, burial depth of 0.8m and soil thermal resistivity of 1.2K.m/W.

The information in this specification is to be used as a guide only. World Wire Cables (Aust) Pty Ltd has taken all due care in compiling the information in this specification but accepts no responsibility for any errors or omissions. All information provided in this specification is covered by copyright.

