




3C XLPE Insulated Medium Voltage Cables 19/33kV, Cu, Anti-termite



Note: The above drawing is for representation purpose only.

Description

Conductor:	Class 2 Plain Annealed Copper
Conductor Screen:	Semi-conductive Compound
Insulation:	XLPE
Insulation Screen:	Semi-conductive Compound
Metallic Screen:	Plain Annealed Copper Wire
Bedding:	PVC 5V-90
Anti-termite Jacket:	Nylon
Sheath:	PVC 5V-90

Core Identification

Red, White, Blue

Sheath Colour

Black

Technical Data

Voltage Rating:	19/33kV
Operating Temperature:	-25°C to +90°C
Short Circuit Temperature:	250°C for 5 sec

Standards Compliance

AS/NZS 1429.1	AS/NZS 3808
AS/NZS 1125	AS/NZS 1660.5.6 (Equivalent to IEC 60332-1)


Characteristics



FLAME RETARDANT



UV STABILISED



-25°C ~ +90°C



TERMITE RESISTANT



GREEN STAR

The information in this specification is to be used as a guide only. World Wire Cables (Aust) Pty Ltd has taken all due care in compiling the information in this specification but accepts no responsibility for any errors or omissions. All information provided in this specification is covered by copyright.





3C XLPE Insulated Medium Voltage Cables 19/33kV, Cu, Anti-termite

Physical & Electrical Characteristics

WWC Product Code	Conductor Size (mm ²)	Conductor Diameter (mm)	Insulation Thickness (mm)	Approx. Overall Diameter (mm)	Min. Bending Radius (mm)		Approx. Weight (kg/m)
					During Installation	After Installation	
*SMMV33C7X3C50NY	50	8.30	8.0	74.3	2406	1604	6.2
*SMMV33C10X3C70NY	70	9.95	8.0	78.0	2526	1684	7.2
*SMMV33C10X3C95NY	95	11.60	8.0	81.8	2649	1766	8.2
*SMMV33C10X3C120NY	120	13.03	8.0	85.1	2757	1838	9.3
*SMMV33C10X3C150NY	150	14.57	8.0	88.6	2871	1914	10.4
*SMMV33C10X3C185NY	185	16.18	8.0	92.9	3009	2006	11.7
*SMMV33C10X3C240NY	240	18.43	8.0	98.0	3174	2116	13.9
*SMMV33C10X3C300NY	300	20.61	8.0	103.1	3339	2226	16.1
*SMMV33C10X3C400NY	400	23.79	8.0	110.3	3573	2382	19.5
*SMMV33C10X3C500NY	500	27.20	8.0	118.3	3834	2556	23.2

© World Wire Cables (Aust) Pty Ltd. All Rights Reserved.

*These cables are non-stocked items subject to lead times.

Cond. Size (mm ²)	Max. D.C. Resistance of cond. at 20°C (Ω/km)	A.C. Resistance of cond. at 90°C, 50Hz (Ω/km)	Operating Induct. (mH/km)	Mutual Capa. (μF/km)	Fault Current Rating (kA/s)		+Current-carrying capacity (A)			
					Cond.	Screen	In Air Touching	In Air Enclosed	In Ground	In ground Enclosed
50	0.387	0.494	0.488	0.143	7.2	7.2	210	159	210	174
70	0.268	0.342	0.465	0.157	10.0	10.1	261	205	256	220
95	0.193	0.247	0.444	0.171	13.6	10.1	313	241	308	261
120	0.153	0.196	0.429	0.185	17.2	10.1	359	277	349	297
150	0.124	0.159	0.415	0.200	21.5	10.1	405	313	390	333
185	0.0991	0.1276	0.403	0.213	26.5	10.1	466	354	441	374
240	0.0754	0.0979	0.388	0.234	34.3	10.1	548	410	513	436
300	0.0601	0.0789	0.377	0.252	42.9	10.1	625	466	579	492
400	0.0470	0.0629	0.364	0.277	57.2	10.1	718	554	656	574
500	0.0373	0.0515	0.354	0.314	71.5	10.1	803	620	728	640

⁺Based on ambient air temperature of 40°C, soil temperature of 25°C, burial depth of 0.8m and soil thermal resistivity of 1.2K.m/W.

The information in this specification is to be used as a guide only. World Wire Cables (Aust) Pty Ltd has taken all due care in compiling the information in this specification but accepts no responsibility for any errors or omissions. All information provided in this specification is covered by copyright.

