




## 3C XLPE Insulated Medium Voltage Cables 3.8/6.6kV, AL



Note: The above drawing is for representation purpose only.

### Description

Conductor:	Class 2 Aluminium
Conductor Screen:	Semi-conductive Compound
Insulation:	XLPE
Insulation Screen:	Semi-conductive Compound
Metallic Screen:	Plain Annealed Copper Wire
Sheath:	PVC 5V-90

### Core Identification

Red, White, Blue

### Sheath Colour

Black

### Technical Data

Voltage Rating:	3.8/6.6kV
Operating Temperature:	-25°C to +90°C
Short Circuit Temperature:	250°C for 5 sec

### Standards Compliance

AS/NZS 1429.1	AS/NZS 3808
AS/NZS 1125	AS/NZS 1660.5.6 (Equivalent to IEC 60332-1)


### Characteristics



FLAME RETARDANT



UV STABILISED



-25°C ~ +90°C



GREEN STAR

The information in this specification is to be used as a guide only. World Wire Cables (Aust) Pty Ltd has taken all due care in compiling the information in this specification but accepts no responsibility for any errors or omissions. All information provided in this specification is covered by copyright.



© World Wire Cables (Aust) Pty Ltd. All Rights Reserved.



## 3C XLPE Insulated Medium Voltage Cables 3.8/6.6kV, AL

### Physical & Electrical Characteristics

WWC Product Code	Conductor Size (mm <sup>2</sup> )	Conductor Diameter (mm)	Insulation Thickness (mm)	Approx. Overall Diameter (mm)	Min. Bending Radius (mm)		Approx. Weight (kg/m)
					During Installation	After Installation	
*SMMV6A2X3C25	25	5.95	2.5	38.6	765	510	1.2
*SMMV6A3X3C35	35	7.04	2.5	41.2	815	544	1.5
*SMMV6A4X3C50	50	8.30	2.5	44.1	873	582	1.9
*SMMV6A6X3C70	70	9.95	2.5	47.9	949	632	2.3
*SMMV6A9X3C95	95	11.60	2.5	51.6	1003	668	3.0
*SMMV6A10X3C120	120	13.03	2.5	54.9	1067	712	3.4
*SMMV6A10X3C150	150	14.57	2.5	58.7	1141	761	3.7
*SMMV6A10X3C185	185	16.18	2.5	62.3	1211	808	4.2
*SMMV6A10X3C240	240	18.43	2.6	68.0	1321	881	5.1
*SMMV6A10X3C300	300	20.61	2.8	74.0	1438	959	6.1
*SMMV6A10X3C400	400	23.79	3.0	82.1	1597	1064	7.3
*SMMV6A10X3C500	500	27.20	3.2	91.0	1769	1180	8.5

© World Wire Cables (Aust) Pty Ltd. All Rights Reserved.

\*These cables are non-stocked items subject to lead times.

Cond. Size (mm <sup>2</sup> )	Max. D.C. Resistance of cond. at 20°C (Ω/km)	A.C. Resistance of cond. at 90°C, 50Hz (Ω/km)	Operating Induct. (mH/km)	Mutual Capa. (µF/km)	Fault Current Rating (kA/s)		+Current-carrying capacity (A)			
					Cond.	Screen	In Air Touching	In Air Enclosed	In Ground	In ground Enclosed
25	1.20	1.54	0.432	0.269	2.4	2.4	108	79	112	89
35	0.868	1.113	0.414	0.297	3.3	3.3	128	94	138	108
50	0.641	0.822	0.394	0.334	4.7	4.7	154	113	164	128
70	0.443	0.568	0.377	0.376	6.6	6.8	190	138	200	154
95	0.320	0.411	0.362	0.421	9.0	9.0	231	169	236	190
120	0.253	0.325	0.351	0.463	11.3	10.1	267	195	272	215
150	0.206	0.265	0.341	0.508	14.2	10.1	302	220	302	246
185	0.164	0.211	0.333	0.550	17.5	10.1	349	251	343	277
240	0.125	0.161	0.324	0.593	22.7	10.1	410	297	395	323
300	0.100	0.130	0.319	0.606	28.3	10.1	472	349	446	374
400	0.0778	0.1016	0.313	0.635	37.8	10.1	548	405	513	431
500	0.0617	0.0816	0.310	0.690	47.3	10.1	629	462	570	479

+Based on ambient air temperature of 40°C, soil temperature of 25°C, burial depth of 0.8m and soil thermal resistivity of 1.2K.m/W.

The information in this specification is to be used as a guide only. World Wire Cables (Aust) Pty Ltd has taken all due care in compiling the information in this specification but accepts no responsibility for any errors or omissions. All information provided in this specification is covered by copyright.

