




4C+E PVC Insulated Orange Circular Cables 450/750V, Cu



Note: The above drawing is for representation purpose only.

Description

Conductor:	Class 2 Plain Annealed Copper
Insulation:	PVC V-90
Sheath:	PVC 5V-90

Core identification

Red, White, Blue, Black, Green/Yellow

Sheath Colour

Orange

Technical Data

Voltage Rating:	450/750V
Operating Temperature:	-25°C to +75°C, Maximum 90°C*
	*Not subject to severe mechanical pressure at temperatures higher than 75°C.
Short Circuit Temperature :	160°C for 5 sec


Standards Compliance

AS/NZS 5000.2	AS/NZS 1660.5.6 (Equivalent to IEC 60332-1)
AS/NZS 3808	AS/NZS 1660.5.1 (Equivalent to IEC60332-3-24)
AS/NZS 1125	


Characteristics



FLAME RETARDANT



UV RESISTANT



-25°C ~ +75°C



GREEN STAR

The information in this specification is to be used as a guide only. World Wire Cables (Aust) Pty Ltd has taken all due care in compiling the information in this specification but accepts no responsibility for any errors or omissions. All information provided in this specification is covered by copyright.



© World Wire Cables (Aust) Pty Ltd. All Rights Reserved.



4C+E PVC Insulated Orange Circular Cables 450/750V, Cu

Physical & Electrical Characteristics

WWC Product Code	Number of cores	Conductor Size (mm ²)	Conductor Diameter (mm)	Insulation Thickness (mm)	Earth Conductor Size (mm ²)	Approx. Overall Diameter (mm)	Min. Bending Radius (mm)		Approx. Weight (kg/km)
							During Installation	After Installation	
1505UA-47	4C+E	1.5	1.56	0.6	1.5	10.1	95	64	175
1502UA-47	4C+E	2.5	2.01	0.7	2.5	11.8	112	74	247
1504UA-47	4C+E	4	2.55	0.8	2.5	13.6	129	86	348
1506UA-47	4C+E	6	3.12	0.8	2.5	14.8	140	93	434

© World Wire Cables (Aust) Pty Ltd. All Rights Reserved.

Conductor Size (mm ²)	†Current-carrying capacity (A)								Maximum D.C. Resistance of conductor at 20°C (Ω/km)
	In Air Spaced	In Air Touching	In Air Exposed to sun	In Air Enclosed	Partially surrounded by thermal insulation Unenclosed	Completely surrounded by thermal insulation Unenclosed	In Ground	In Ground Enclosed	
1.5	16	15	12	14	12	8	18	18	13.6
2.5	23	22	17	20	17	11	25	25	7.41
4	31	29	23	25	23	15	33	33	4.61
6	40	37	29	33	30	19	42	42	3.08

†Based on ambient air temperature of 40°C, soil temperature of 25°C, burial depth of 0.5m and soil thermal resistivity of 1.2K.m/W.

The information in this specification is to be used as a guide only. World Wire Cables (Aust) Pty Ltd has taken all due care in compiling the information in this specification but accepts no responsibility for any errors or omissions. All information provided in this specification is covered by copyright.

